



Rec'd PCT/PTO 12 OCT 2004



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 20 MAY 2003

WIPO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

Signed

Stephen Horrell

Dated

7 October 2002

Best Available Copy

Patents Act 1977
(Rule 16)

THE PATENT OFFICE
23 APR 2002
RECEIVED BY FAX

The Patent Office
TRADE MARKS

23 APR 02 E712990 C65900
P01/7700 0.00-0209143.7

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

23 APR 2002

The Patent Office

Cardiff Road
Newport
Gwent
NP10 8QQ

1. Your reference

BR8809A (UK)

BR 8812 (UK)

2. Patent application number (The Patent Office will fill in this part)

0209143.7

3. Full name, address and postcode of the or of each applicant (underline all surnames)

EMHART LLC
DRUMMOND PLAZA OFFICE PARK
1423 KIRKWOOD HIGHWAY
NEWARK, DELAWARE 19711, U.S.A.

Patents ADP number (if you know it)

8325227002

If the applicant is a corporate body, give the country/state of its incorporation

USA/DELAWARE

4. Title of the invention

IMPROVED PEEL-TYPE BLIND RIVET

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

DARRIN MAURICE SHAYA,
IAN STEPHEN BELL
BLACK & DECKER
210 BATH ROAD
SLOUGH,
BERKSHIRE SL1 3YD
UNITED KINGDOM

Patents ADP number (if you know it)

7570971001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

YES

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

| | |
|----------------------------------|----|
| Continuation sheets of this form | 0 |
| Description | 13 |
| Claim(s) | 3 |
| Abstract | 1 |
| Drawing(s) | 4 |

10. If you are also filing any of the following, state how many against each item.

| | |
|--|---|
| Priority documents | 0 |
| Translations of priority documents | 0 |
| Statement of inventorship and right to grant of a patent (Patents Form 7/77) | 1 |
| Request for preliminary examination and search (Patents Form 9/77) | 0 |
| Request for substantive examination (Patents Form 10/77) | 0 |
| Any other documents (please specify) | 0 |

11.

I/We request the grant of a patent on the basis of this application

Signature

I S Bell

Date: 23 April 2002

12.

Name and daytime telephone number of person to contact in the United Kingdom

IAN STEPHEN BELL 01753 500788

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

1

IMPROVED BLIND RIVET

The present invention relates to an improved blind rivet, more particularly to a peel-type blind rivet which is particularly suitable for anchoring in relatively soft materials such as wood or plastics.

Conventional blind riveting techniques which are normally used to secure together two or more workpieces, utilise a blind rivet having a tubular shank with an enlarged head at the operative end thereof such that the shank can pass through a preformed hole in extending between two workpieces, whereby a mandrel disposed within the tubular rivet body having an enlarged head is then used to compress the rivet body on the blind side (ie. behind the workpieces to be set) to create a bulge which will compress the workpieces against the enlarged head.

However, where the blind side workpiece material is both of substantial thickness and is relatively soft, modified peel-type blind rivets have been employed which operate in a significantly different manner whereby the end of the rivet body, remote from the head (the blind side), is caused to split and form into a series of radially extending legs which compress and engage with the soft material into which the peel-type blind rivet has been displaced, whereby these legs are restrained remote from the head-end of the rivet, once set by providing appropriate means to arrest continued splitting or deformation of such legs. Existing peel-type blind rivets are divided into two distinct groups, the first of which has its body provided with a weakened region which will either be cut to form the required legs by cutting edges formed on the mandrel head or have preformed, weakened regions (such as channels) within the rivet body along which the body will rupture when the mandrel head is drawn into the rivet body. These type of rivets normally employ a dual thickness rivet body whereby the weakened regions are of a reduced thickness as compared to the main rivet body such that continued splitting of the rivet is arrested when the mandrel head engages with the thickened portion of the rivet body. Blind rivets of this type are discussed in EP344,005 and EP328,314.

BRBB09A (UK)

An alternative, preferred, form of peel-type blind rivet employs the use of preformed slots formed in the free end of the rivet body, which slots define the legs to be displaced during the setting operation. One example of a peel-type blind rivet of this type is disclosed in the applicants earlier British Patent No. GB 2332722.

5

However, one of the disadvantages of peel-type blind rivets employing preformed slots is the complex manufacturing process required to form the slots in the shank of the rivet body requiring a specialised punch, usually comprising a cylindrical main body for receipt within the hollow rivet body and having four cutting arms extending radially outwards of this main body portion for cutting through the rivet shank to form the slots having substantially parallel sides. Since the width of the slots is relatively narrow, the corresponding cutting blades from the punch must also be relatively narrow and thus are subject to rapid wear due to the high forces exerted on these cutting blades. As such, conventional rivets having preformed slots are relatively expensive due to the associated costs of both manufacturing the complex punches and their high wear and failure rate.

10
15

Therefore an object of the present invention is to alleviate the aforementioned problems and to provide an improved peel-type blind rivet, and a punch for forming slots in such rivets.

20

According to the present invention there is provided a peel-type blind rivet assembly for setting in relatively soft material, this rivet assembly comprising:

25

an elongate tubular body having a shank disposed about a shank axis and a preformed head at a first end thereof and an expandable portion at the opposed end of the shank which is remote from the head, and which expandable portion is formed by a plurality of slots, which slots terminate remote from this first end;

30

the rivet assembly further comprising a mandrel having a stem extending through and co-axial with the tubular body, this mandrel further having a head having a maximum external diameter greater than the internal diameter of the body;

BR8809A (UK)

wherein, at least one of said plurality of slots increases in width as it extends from an outer surface to an inner surface of the shank. In this manner, the slot itself is seen to taper as it increases in radius.

- 5 Preferably, the side walls of the at least one slot will be linear or alternatively they could be slightly curved, usually so as to be convex.

- 10 Usually, each of the plurality of slots will be equally spaced about the circumference of the tubular body so that the angular displacement between adjacent slots about the shank axis is constant.

In a preferred embodiment, the plurality of slots will comprise three slots disposed at substantially 120° about the shank axis.

- 15 Usually, the axial inner end of at least one of the plurality of slots will be radially inclined so that the at least one slot is longer where it is adjacent to and intersects the inner surface of the shank, as opposed to a shorter length where the slot engages and is adjacent to the outer surface of the shank.

- 20 Furthermore, this rivet assembly may have a shoulder formed on the mandrel head extending between the mandrel stem and an outer surface of the mandrel head, which shoulder extends substantially perpendicular to the shank axis. Additionally, the opposed end of the shank may also comprise a substantially flat surface, again substantially perpendicular to shank axis, for complimentary flush fitting with this
25 shoulder.

It is preferred that the wall thickness of the body is constant along its axial length and it is also usual that the external diameter of the shank is constant along this
30 length.

- Preferably, the mandrel stem will have a reduced diameter section adjacent to its shoulder so as to form a recess within the mandrel stem so that material displaced

BR8809A (UK)

from the rivet body during the setting operation may be deformed into this recess to restrain the set mandrel head following the setting operation of the rivet.

5 It is also preferred that the maximum diameter of the mandrel head is equal to the diameter of the rivet shank so that the preformed hole into which the rivet is to inserted need only be sufficient diameter to receive the diameter of the rivet shank.

10 According to a further aspect of the present invention there is also provided a punch for manufacturing the tubular body of a peel-type blind rivet of the type having an array of tapered slots formed in an opposed end of the shank, whereby the punch will comprise an elongate solid body having a polygonal cross section wherein at least one convergence zone formed on an end face of the punch by the tapering convergence of two adjacent side walls forms a slot cutting element. In this manner, these cutting elements will overlie the end face of the tubular rivet so as to form slots
15 in the wall of the tubular body which increase in width between an outer surface and an inner surface thereof.

Usually the convergence zone of each pair of adjacent side walls will form a cutting element on this end face, each of which will abut and form an appropriate slot
20 in the rivet body.

In one embodiment, the adjacent side walls of the punch may be curved to provide a substantially curved cutting element. Where such walls are curved they are usually concave.
25

Preferably, the or each of the cutting elements formed on the end face of the punch will be radially inclined relative to a longitudinal axis of the punch, in this manner being able to form inclined inner ends of the slot in the rivet body.

30 The punch will, preferably, further comprise a cylindrical projection extending from the end face which is coaxial with a longitudinal axis of the punch, whereby this

BR8809A (UK)

projection is for receipt within a central bore of the tubular body of the rivet to align the punch coaxial with that rivet during the slot forming procedure.

It is preferred that the polygonal cross section of the punch will comprise or
5 define a regular polygon wherein each side of the polygonal is substantially identical and uniform, preferably having equal angles between each adjacent side face of such polygonal.

Preferably, the punch will have a substantially triangular cross section forming
10 three slots within an appropriate rivet body.

There will now be described, by way of example only, a preferred embodiment of the present invention with reference to the accompanying illustrative drawings in which:
15

Figure 1 shows a partial cross sectional view of a peel-type blind rivet according to the prior art; and

Figure 1a is an end view of the rivet body of Figure 1; and

Figure 2 is a partial cross section of the rivet of Figure 1 shown in a set position;
20 and

Figure 3 shows a partial cross section of a peel type blind rivet according to the present invention; and

Figure 4 is a plan view from one end of the body of the blind rivet of Figure 3;
and

25 Figure 5 shows the peel-type blind rivet of Figure 3 in a set configuration; and

Figure 6 is a plan view of the shank of a peel-type blind rivet according to a second embodiment of the present invention; and

Figure 7a shows a plan view from one end of a punch tool used to form the body of the blind rivet of Figure 3; and

30 Figure 7b is a side view of the punch tool of Figure 7a when viewed along the arrow X; and

Figure 7c is a side view of an alternative embodiment of the punch tool of Figure 7a.

A peel-type blind rivet assembly (10), according to the prior art, is seen in Figure 1. This blind rivet assembly (10) comprises a tubular body (2) containing a mandrel (4), and having a head (8) formed by a flattened flange portion, presenting a circumferential shoulder (9) for engagement with a first workpiece. Four equally spaced elongate slots (12) are provided in the end (14) of the shank (6) remote from the head (8) and provide an expandable portion (16) of the shank, dividing this expandable end portion into four distinct legs (17) therebetween. The base (18) of each slot (longitudinally remote from an end (14) of the shank) is axially inclined relative to an axis of the shank such that the length of the slot is longer where it is adjacent to the inner surface of the body (adjacent to the bore (20)) and is of a shorter longitudinal length where it is adjacent to the outer surface of the body.

15

The mandrel (4) is of conventional design comprising a head (26) having an underhead portion (28) which increases progressively in diameter from the mandrel stem (119) towards the maximum diameter of the mandrel head (26). In this embodiment the underhead shape (28) provides a radially inclined shoulder portion. Adjacent to the shoulder portion (28) the mandrel stem has a narrowed portion (34) forming an effective recess (35) adjacent to the mandrel head.

20

The mandrel stem is further provided with a breakneck (36), as is conventional to blind rivets, and effectively comprises a narrowed neck portion designed to break when a predetermined load is applied across this weakened region.

25

Figure 2 shows the rivet assembly (10) in a set configuration when used in a particular application in a soft material. Here, the prior art peel-type blind rivet assembly (10) is used to restrain a first, relatively thin, workpiece (50) (usually of metal) onto a relatively thick, considerably softer workpiece (52) which will usually be wood or plastics material. The first workpiece (50) is placed adjacent to the second workpiece (52) and a hole (54) formed therebetween, usually by a drill. The

30

BR8809A (UK)

rivet assembly (10) is then inserted into the hole (54) so that the shoulder (9) of the rivet head (8) engages with the outer surface of the workpiece (50). The rivet is then set in a conventional manner of setting a blind rivet (ie. by pulling the mandrel (4) downwardly as viewed in Figure 1) whilst restraining displacement of the mandrel head (8) using a conventional rivet setting tool. As the rivet is set, the curved shoulder portion (28) beneath the mandrel head (26) engages with the weakened tail region (16) of the rivet body (2) so that the separate legs (17) of the weakened region (16) are displaced outwardly from the rivet body (2) and so as to cut through and into the second workpiece (52) effectively compressing the soft material (70) which has been displaced by such cutting action.

This prior art embodiment further includes a circumferential groove (22) which has been preformed in the rivet body so as to be adjacent to the bases (18) of the slots (12), whereby the legs (17) of the deformed rivet body tend to bend about such groove (22). Furthermore, the legs (17) themselves are further bent or curved by the radial forces applied by the radial shoulder (28) as it engages the legs during the bending or deforming operation.

As the head (26) of the mandrel (4) is displaced towards the head (8) of the rivet body (2), the setting load increases due to the increased resistance as the head approaches the groove (22) and the increased setting load serves to help collapse the groove (22) causing rivet body material adjacent to the groove (22) to be displaced inwardly into the recess (35) about the mandrel stem, thus locking the mandrel head (26) in engagement with the set rivet body. The setting load continues to increase until the rivet fails at the breakneck (36) in a conventional manner. In this embodiment the mandrel head is thus retained within the set rivet.

Whilst the prior art device performs adequately, it has been determined that the curved nature of the deformed legs (17) in the set configuration (arising from bending thereof caused by the interaction with the curved shoulder (28) of the mandrel head (26)) results from anticlastic flow of material on the inner surface of such legs as they are stretched into the curved configuration shows in Figure 2. This results in the leg

BR8809A (UK)

portions becoming slightly thinner than the main rivet body thickness and thus such deformed legs are thinner and weaker than the main, undeformed, region of the shank.

5 In addition, this prior art device comprises an additional manufacturing step in forming the indentation (22) which is able to react with the curved shoulder (28) to cause the rivet body material (72) to flow into the recess (35) to effect restraint of the mandrel head in the set rivet.

10 It will also be understood that, as the legs of the rivet body (2) bend during setting, the inner surface of the legs tend to increase in length. Material from the rivet body to accommodate this stretching will be provided from the section of the leg at that point in a movement known as anticlastic movement. This, in order to assist the movement of this material without creating undue stress, the base (18) of the slots (12) are inclined as shown in Figure 1.

15 The preferred embodiment of the present invention is now shown in Figure 3 and is effectively a modified version of the prior art peel-type blind rivet (10) as shown in Figure 1 and like parts of the rivet assembly of the present invention will now be identified by the same reference numbers to those used in Figure 1 but will
20 include the prefix (1) or (10) for distinction.

Figure 3 shows a modified peel-type blind rivet assembly (110) of substantially similar configuration to the rivet assembly (10) and again comprises a tubular body (102) with a similar mandrel (104). The rivet body head (108), mandrel breakneck (136) and mandrel shank (106) are substantially identical to those shown in Figure 1.
25 Again the mandrel comprises a mandrel head (126) and the mandrel stem has a recess portion (134) adjacent to this mandrel head to form a recess (135) again similar to that discussed with reference to Figure 1.

30 The significant difference of the blind rivet assembly (110) resides in the shoulder portion (128) extending between the mandrel stem (119) and the maximum outer diameter (131) of the mandrel head (126). As seen in Figure 3, this shoulder

BRE209A (UK)

portion (128) is substantially perpendicular to the rivet axis (200) and presents a substantially flat face for flush engagement with a substantially flat end surface (114) of the rivet body (102). Formation of such a mandrel is considerably simplified to that of the mandrel (4) as seen in Figure 1.

5

The second notable modification to the rivet assembly (110) is that the shank (106) is of constant diameter along its entire axial length and of constant thickness (in particular, there is no groove portion as seen in the rivet assembly (10)), thereby negating the additional manufacturing step involved in the creation of such a groove.

10

In addition, in the preferred embodiment of the rivet assembly of the present invention (110) shown in Figures 3 and Figures 4, the rivet body (102) has three longitudinally extending grooves (112) extending inwardly from the end (114) of the rivet body remote from the head (108) (as opposed to four in Figure 1) and, as particularly seen in Figure 4, these grooves (112) increase in width from an outer surface (127) of the shank (106) towards an inner surface (129) of the rivet body (102) (which surface (129) defining the rivet bore (120)). Also, as seen in Figure 3, the assembly (110) has bases (118) of the slots (112) which are again inclined inwardly from the outer surface (127) of the body (102) towards the inner surface (129) of such body. In this manner, the slots (112) are longer adjacent to the inner surface (129) of the rivet body (102) than when adjacent to the outer surface (127) of the body (102). However, this is an optional feature and these bases (118) may in fact be flat (or substantially perpendicular to the rivet axis (200)).

25

The slots (112) provide a significant advantage over the prior art slots (12) of Figure 1 in providing for an improved manufacturing process. In particular and with reference to Figure 7a and 7b, a more robust metal extrusion punch (280) can be used in the formation of these slots (112) and, hence, the rivet body (102). Firstly, referring back to the rivet assembly (10) shown in Figure 1a, it will be appreciated that the metal extrusion punch required to form the grooves (12) will comprise a cylindrical support body (to be received within the bore (20) of the tubular rivet body (2)) with four perpendicular narrow cutting blades extending from this cylindrical

30

BR8809A (UK)

tube for engaging the rivet body (102) to effectively cut the elongate slots (12) along such body (2) as the punch is passed through the bore (20). Both the formation of such a extrusion punch is relatively complex due to the relatively thin projections extending therefrom, and these relatively thin projections are subject to comparatively high stresses and are subject to significant wear and damage.

However, referring back to Figure 7a, the extrusion punch (280) developed for the current invention is considerably simplified and comprises a triangular extrusion punch which, in the embodiment shown in Figure 7a, has an axially extending location cylinder (281) extending from an end face thereof. The location cylinder (281) is of corresponding size to the bore (120) of the rivet body (102) of Figure 3 and serves to locate the punch (280) centrally of the rivet body. As such, a substantially flat end face (282) of the elongate punch (280) comprises three cutting elements (285) each formed as a convergence zone on this end face formed by the tapering convergence of two adjacent side walls of the punch. This convergence zone (282) (shown as a shaded region in Figure 7a) may be considered as the surface of the end face (282) formed between adjacent side walls of the punch (280) which, when aligned with the rivet body (102) are aligned with the shank walls so as to engage the end face (114). As shown in Figure 7a this region is defined as the face area between the projection (281) and the dotted lines indicating the outer diameter of the shank (106). As such, it will be appreciated here that whilst for ease of manufacturing the punch (280) is shown to have a triangular cross section, the apex of this cross section formed by the exact intersection of the side walls could be omitted since such apex does not actually engage with the rivet body during the punch operation. However, removal of such ends would involve an additional manufacturing step and is unnecessary. What is clear, is that the cutting elements (285) are not necessarily formed in the end face at the exact apex of the converging side faces but may be set slightly back from such apex. However, it is the convergence zone of the side faces which forms the appropriate cutting element.

In addition, it will be appreciated that in the embodiment shown in Figure 7a and 7b the punch (280) is provided with a substantially flat end face (282) extending

BR8809A (UK)

perpendicular to an axis (B) of such a punch, which will form substantially flat bases (18) of the slots (112) during the slot forming operation. Alternatively, the cutting elements (285) could be inclined relative to the axis (B) of the punch (280) as shown in the alternative embodiment as shown in Figure 7c, so as to form the inclined bases (118) of the slots (112) of the embodiment of Figure 3. It will be further appreciated the projection (281) could, if required, be omitted and alternative alignment means between the punch (280) and rivet body (102) employed.

In operation, the rivet body (102) is formed in a conventional manner following which the extrusion punch (280) is engaged with the free end (114) thereof so as to form the slots (112) as shown in Figure 4. This improved punch (280) is more readily manufactured as a simple polygonal shape providing for greater strength since its cutting elements are considerably larger and more robust than those utilised in the prior art. Since this punch is more robust and easier to manufacture, it results in a reduction in production costs of such tools and is less prone to wear and failure.

Referring now to Figure 5, showing the rivet assembly (110) in its set configuration, the manner of setting the rivet (110) is substantially identical to that of rivet assembly (10), whereby again the mandrel (104) is engaged by a rivet setting tool and displaced relative to the rivet body (106) once the rivet assembly (110) has been inserted in a preformed hole (154). However, the specific performance of the improved rivet assembly (110) will now be described.

As a setting load is applied (in a direction illustrated by arrow (F) in Figure 3) a compressive load is exerted by the flat shoulder (128) of the mandrel head (126) onto the corresponding flat end (114) of the rivet body, causing the legs (117) (defined between the array of slots (112)) to resiliently deform and to be splayed radially outward of the body (102) until the shoulder (128) engages with the inner surface (127) of these splayed legs (117). In this manner, there is now a linear displacement force created by linear engagement of the linear (non-curved) shoulder (128) with this inner surface (127) so that the legs are displaced in a cantilever manner about their engagement portion (157) with the main part of the shank (106). Here, the legs (117)

BR8809A (UK)

are not themselves bent during this setting operation but are maintained in their original straight configuration and thus do not undergo any stretching or anticlastic deformation. In this way the set legs shown in Figure 5 are considerably stronger than those shown for the prior art embodiment shown in Figure 2, whilst the legs (117) themselves are still splayed so as to cut through the softer workpiece (normally wood) (52) in a similar manner to that shown in Figure 2 to compress the material between these legs and the outer workpiece (150). These non-deformed legs (117) retain their original thickness following setting and not being curved, so as to be stronger than those of the prior art and, as seen in Figure 5, which could be prone to deformation if a pull out force is applied to the set rivet.

As the mandrel head (126) is again displaced further into the rivet body (106) towards the head (108), the setting load increases due to the increased resistance incurred by the mandrel head (126) towards the end (118) of the slots (112), due to the main shank (106) of the body (102) being resistant to radial deformation since it does not have slots (112) extending therethrough. As this setting load increases, the substantially flat shoulder (128) of the mandrel head (126) is no longer able to apply a radial displacement force to the legs (117) and thus effects a compressive force on the rivet body (in direction F) causing flow of the rivet body material into the recess portion (135) formed about the narrowed section (136) of the mandrel stem to again effect engagement between the mandrel head and the rivet body in the set position. Increased loading force on the mandrel will then result in the mandrel failing at the breakneck (136) in a conventional manner. This modified assembly (110) provides additional strength in comparison to the prior art resulting from the cantilevered displacement of the performed legs (117) during the setting operation, thereby maintaining the thickness of the leg sections to be the same as the thickness of the main rivet body wall following the setting operation, providing greater sectional strength.

Whilst this preferred embodiment shown in Figures 3 to 5 has utilised the formation of three slots (112) to form three corresponding legs (117) of equal size (such slots being displaced at equal angles about the axis of the rivet), it will be

BR8809A (UK)

appreciated that alternative numbers of legs and associated slots could be employed. If four slots were required to form four legs, then a substantially square punch could be employed, utilising the invention as discussed with relation to the setting tool (280) shown in Figure 7. If required, higher polygonal numbers could also be employed by
5 using punches having hexagonal or higher order cross sectional configurations. In addition, whilst the punch design according to the present invention comprises regular polygons as shown in Figure 7, the side faces of such punches need not be straight but could be curved to produce curved side walls of slots (212) within the rivet body (202), as shown in the alternative embodiment in Figure 6 which have been formed by
10 a substantially concave triangular punch to produce convex edges to the tapered slots (212) in such embodiment.

CLAIMS

1. A peel type blind rivet assembly for setting in relatively soft material, said
5 rivet assembly comprising :
an elongate tubular body having a shank disposed about a shank axis and a
preformed head at a first end thereof and an expandable portion at the opposed end of
the shank remote from the head and formed by a plurality of slots, which slots
terminate remote from said first end;
- 10 a mandrel having a stem extending through and co-axial with said tubular
body, which mandrel further having a head having a maximum external diameter
greater than the internal diameter of the body; wherein,
at least one of said plurality of slots increases in width as it extends from an
outer surface to an inner surface of said shank.
- 15 2. A blind rivet assembly as claimed in claim 1 wherein the side walls of said at
least one slot are curved.
3. A blind rivet assembly as claimed in either of the preceding claims wherein
20 each of said plurality of slots are equally spaced about the circumference of said
tubular body so that the angular displacement between adjacent slots about the shank
axis is constant.
4. A blind rivet assembly as claimed in any one of claims 1 to 3 wherein said
25 plurality of slots comprises three slots.
5. A blind rivet assembly as claimed in any one of the preceding claims wherein
an axial inner end of at least one of said plurality of slots is radially inclined so that
said at least one slot is longer adjacent said inner surface of said shank than adjacent
30 said outer surface of said shank.

BR8509A (UK)

6. A blind rivet assembly as claimed in any one of the preceding claims wherein said mandrel head forms a shoulder between a mandrel stem and an outer surface of said mandrel head, which shoulder extends perpendicular to said shank axis.

5 7. A blind rivet assembly as claimed in any one of the preceding claims wherein the wall thickness of said body is constant along its axial length.

8. A blind rivet assembly as claimed in claim 8 wherein the external diameter of said body is constant along its axial length.

10

9. A blind rivet assembly as claimed in any one of the preceding claims wherein said mandrel stem has a reduced diameter section adjacent said shoulder.

10. A blind rivet assembly as claimed in any one of the preceding claims wherein
15 said maximum diameter of said mandrel head is equal to the diameter of said body.

11. A punch for manufacturing said tubular body of a peel type blind rivet as
claimed in any one of the preceding claims, comprising an elongate solid body
having a polygonal cross section wherein at least one convergence zone formed on an
20 end face of said punch by the tapering convergence of two adjacent side walls forms a
slot cutting element.

12. A punch as claimed in claim 11 wherein the convergence zone of each pair
of adjacent side walls forms a cutting element on said end face.

25

13. A punch as claimed in claim 11 or claim 12 wherein said adjacent side walls
are curved.

14. A punch as claimed in claim 13 wherein said curved walls are concave.

30

16

15. A punch as claimed in any one of the claims 11 to 14 wherein the or each cutting element on said end face is radially inclined relative to a longitudinal axis of said punch.

5 16. A punch as claimed in any one of claims 11 to 15 having a cylindrical projection extending from said end face, and co-axial with a longitudinal axis of said punch, said projection for receipt within a central bore of said tubular body to align said punch therewith.

10 17. A punch as claimed in any one of claims 11 to 16 wherein said polygonal cross section defines a regular polygon.

18. A punch as claimed in any one of claims 11 to 17 which has a substantially triangular cross section.

15

19. A blind rivet assembly substantially as herein described with reference to the accompanying drawings.

20. A punch for manufacturing a tubular body of a peel type blind rivet, of the type according to any one of claims 1 to 10, substantially as herein described with reference to the accompanying drawings.

ERR509A (UK)

17

ABSTRACT

IMPROVED BLIND RIVET

5

The invention is directed to a peel-type blind rivet assembly (110) for setting in relatively soft material (152) and comprising an elongate tubular body (102) having a shank (106) with a enlarged head (108). A free end (114) of the shank, remote from the head (108), has an expandable portion formed by a plurality of slots (112) extending partway along the shank from this remote end (114). A mandrel (104) has a stem, and a mandrel head (126) with a maximum external diameter greater than the internal diameter of the body (102), wherein at least one of the plurality of slots increases in width as it extends from an outer surface of the shank towards an inner surface of the shank.

15

There is also provided a punch for forming the tapered slots (112) in the rivet body (280), comprising an elongate solid body having a polygonal cross section wherein at least one convergence zone formed on an end face of the punch by the tapering convergence of two adjacent side walls forms a slot cutting element (285).

20

BR8809A (UK)




Fig 1




Fig 1a




Fig 2




Figure 3




Fig 4








Fig 6





**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.